

LASCO PUSH

NO GLUE. GREAT FOR REPAIRS.

LASCO Fittings Inc. now has a quick and simple solution for your irrigation needs - Removable Push Fittings for use with Schedule 40, Class 200 / SDR-21 or IPS Flex Pipe. Available in 1/2", 3/4" and 1" sizes.



FEATURES & BENEFITS

- No Primer or Glue Required
- No VOCs
- Simply clean and de-bur the pipe and push on
- Can install wet – no need to empty water out of trenches
- Once installed, the fitting will rotate to easily line up tees and elbows
- Can be pressurized immediately – no need to wait
- Stainless Steel Retainer Ring
- Max. working pressure: 140 psi
- For irrigation only – can be used on mainlines*!
- Patent Pending
- Removes easily with PUSH Removal Tool!

APPLICATIONS

Residential & Commercial
Golf Course

HOW TO INSTALL

1. Cut pipe to the desired length and de-bur it.
2. Clean the end, ensuring that it is debris-free.
3. While twisting, insert the pipe into the fitting. Make sure the pipe passes through both O-rings to be fully seated inside the clear portion of the fitting.

LASCO Push Fittings are for non-potable irrigation applications only; must be used after the backflow preventer. LASCO Push Fittings are for cold water use only; not for above ground applications, must be buried. LASCO Push Fittings are not to be used in a dwelling.



**PERFECT
FOR
REPAIRS**

